

Atomic Colors

The Atomic Colors is a specially designed color scroller accessory which fits onto the front of the original Atomic 3000 DMX and also the new Atomic 3000 LED - allowing up to ten brightly colored strobe and blinder effects. In combination with the Aura backlight and main output of the Atomic 3000 LED it also delivers stunning threedimensional eye candy looks.

Physical

Length: 470 mm (18.5 in.) Width: 273 mm (10.7 in.) Height: 102 mm (4.0 in.) Weight: 2.5 kg (5.5 lbs.)

Color gel thickness: 0.075 mm (0.003 in.) - 0.125 mm (0.005 in.)

Dynamic Effects

Color gel scrolling: 10 standard colors supplied, custom color gel strings can be

fabricated by customer

Control and Programming Control options: DMX DMX channels: 1 or 2

Cooling fan speed control: Onboard control panel, DMX

Gel scrolling speed, 'gel saver' mode, light-activated fan operation: Onboard control

Setting and addressing: Three-button LED control panel DMX compliance: USITT DMX512/1990

Construction

Color: Black Finish: Electrostatic powder-coated

Housing: Steel

Protection rating: IP20

Installation

Location: Indoor use only, mounted on Atomic fixture

Mounting points: Fastens to Atomic fixture

Orientation: Any Connections

Combined power and DMX data from Atomic fixture: 4-pin XLR

Flectrical

DC power: 24 V (+/- 10%) DC current: 0.55 A (max.)

Power source when used with xenon tube-based Atomic 3000 DMX: MPU-02 or MPU-

08 external PSU

Cooling: Forced air (4-speed fans)

Maximum ambient temperature (Ta max.): 40° C (104° F) Minimum ambient temperature (Ta min.): 10° C (50° F)

Included I tems

10-color gel string (installed): P/N 91611090 5 m power/data cable, 4-pin XLR: P/N 11821014

User manual

Accessories MPU-02 Power Supply Unit*: P/N 91611084 MPU-08 Power Supply Unit*: P/N 91611085

*For use with original Atomic 3000 DMX only. Do not use a PSU when installing on Atomic

3000 LFD

Ordering Information

Atomic Colors for Atomic 3000 DMX and Atomic 3000 LED: P/N 91611086



