



VM-400HDCPxI

1:4 4K60 4:2:0 DVI DA



The VM-400HDCPxI is a 4K@60Hz (4:2:0) 1:4 distribution amplifier for HDMI signals via single-link DVI. It takes one DVI input, equalizes and reclocks the signal and distributes it to four identical outputs. With the appropriate adapter, it distributes signals having resolutions up to 4K@60Hz (4:2:0), WUXGA and 1080p.

FEATURES

- Max. Data Rate - 10.2Gbps (3.4Gbps per graphic channel).
- Resolution Support - Up to 4K@60 (4:2:0), WUXGA and 1080p.
- HDCP Compliance.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal integrity to travel longer distances.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - An intelligent EDID handling and processing algorithm that ensures Plug and Play operation for HDMI systems.
- Default EDID - For fast and efficient connection of the unit.
- 3D Pass-Through.
- USB Port - For firmware upgrading.

TECHNICAL SPECIFICATIONS

INPUT:	1 DVI-I connector.
OUTPUTS:	4 DVI-I connectors.
PORT:	1 USB for firmware upgrade.
MAX. DATA RATE:	10.2Gbps (3.4Gbps per graphic channel).
STANDARDS COMPLIANCE:	Supports HDMI and HDCP.
CONTROLS:	EDID Setup button.
INDICATOR LEDs:	IN, OUT 1 to 4 LEDs.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
POWER CONSUMPTION:	5V DC, 1.1A.
DIMENSIONS:	18.8cm x 11.5cm x 2.5cm (7.38" x 4.53" x 1.0") W, D, H.
WEIGHT:	0.3kg (0.67lb).
INCLUDED ACCESSORIES:	Power supply.